



SUREBOND

S.R.B. Stain & Rust Buster

★ CONTRACTOR GRADE FOR RESIDENTIAL AND COMMERCIAL PROJECTS ★

SUITABLE SUBSTRATES:

Ideal for concrete and clay pavers, concrete flat work and retaining walls. It can be used on manufactured and natural stone, concrete block and wet cast products. It works on both horizontal and vertical applications. Not for use on asphalt.

PRODUCT DESCRIPTION:

S.R.B. is a powerful, concentrated spot cleaner which dislodges and removes common stains such as moss, mildew, leaf, rust, blood, beverage spills and non-greasy food stains.

S.R.B.'s concentrated biodegradable formula allows for a full spectrum of dilutions matched to your cleaning needs.

S.R.B.'s unique Clean Rinse Technology quickly and easily rinses away residue with a high or low pressure washer.

S.R.B. is the cleaner of choice by contractors for both routine maintenance and restoration. It can be used to prepare your surface for sealing in tandem with Oil Extractor for oil stains, SureClean for surface cleaning and Efflo Off for efflorescence removal. S.R.B can be used to clean and maintain Surebond sealed surfaces as it is compatible with all Surebond sealer products with proper dilution, dwell time and application. Misuse may damage sealer.

Features	Benefits
What makes S.R.B. different?	
Powerful	• Cleans a Wide Range of Non-Greasy Stains
Fast Acting	• Works in Minutes
Clean Rinse Technology	• Does Not Leave Cleaner Residue on Surface
Concentrated	• Dilute for Strength to Match Your Cleaning Needs

SURFACE & AIR TEMPERATURES:

Excessively high or low temperatures will produce poor results. Best cleaning results are obtained when air and surface temperatures are 40°F or above. Do not clean when temperatures are below freezing or will be overnight. If freezing conditions exist, allow adequate time for surface to thaw. If air temperatures exceed 90°F, flash cool the surface with water before applying product. Do not allow product to dry on a hot surface. Always rinse thoroughly while cleaner is still wet on surface.

PREPARATION/PRE-TESTING:

Sweep and remove all loose soil and debris from the surface. Protect adjacent and surrounding surfaces not intended to be cleaned. Before using S.R.B., test on a small, inconspicuous area to determine the suitability, dilution and correct dwell time of this product for your surface. Allow test areas to dry thoroughly before evaluating final appearance and results.



DILUTION:

S.R.B. is a concentrated spot cleaner that needs to be diluted prior to use. Amount of dilution is dependent on the level of strength needed for the severity of the stain and the type of surface. Only use what is needed to efficiently clean as under dilution (too strong) may cause damage to the substrate. See 'Coverage Rates' for amount of product needed for your cleaning needs. To make a dilution that is ready to use, pour the desired amount of S.R.B. into an empty and clean container, then fill the balance of the container with water and mix.

Dilution Ratio (Water: S.R.B.)	S.R.B. needed for 1 ready to use quart	S.R.B. needed for 1 ready to use gallon	Application
3:1	8 OZ.	32 OZ.	Max strength for difficult cleaning
15:1	2 OZ.	8 OZ.	Standard dilution for general purpose cleaning
30:1	1 OZ.	4 OZ.	Moderate dilution for light soil & cleaning on sealed surfaces

APPLICATION INSTRUCTIONS:

Apply dilution of S.R.B. using a low-pressure sprayer such as a garden sprayer or spray bottle. Allow cleaner to soak into the surface for 5 to 10 minutes. Scrub with a brush to agitate and break down stains. Brushless cleaning requires two applications of S.R.B. spaced several minutes apart without allowing it to dry on the surface. The first pass is to penetrate and the second is to lift the stain out. Use a hot water high pressure washer to draw out and further break down surface stains. Rinse surface thoroughly. It may be necessary to use stronger concentrations



★ CONTRACTOR GRADE FOR RESIDENTIAL AND COMMERCIAL PROJECTS ★

and to perform secondary cleanings to remove heavier, deep set stains. Only use as much pressure as needed to thoroughly clean as excessive high pressures can damage substrates.

COVERAGE*:

APPLICATION	SQ FEET	SQ METERS
All Surfaces	100 - 250	9.3 - 23.2

*Coverage rates will vary from 100-250 sf per gallon of dilution depending on the surface porosity, texture, severity of staining, application method and other local conditions. Coverage based on single treatment. Some applications may require additional treatments.

PACKAGING / SIZES:

12 - quart containers per case

CONTAINER HANDLING/STORAGE: Store locked up in a well-ventilated place. Keep Cool. Do not allow to freeze.

DISPOSAL: Dispose of contents and container to appropriate waste site or reclaimer in accordance with all applicable laws, regulations, and product characteristics at time of disposal.

SHELF LIFE: 2 years if properly stored

PRECAUTIONARY INFORMATION:

KEEP OUT OF REACH OF CHILDREN • Read label before use • Use only outdoors in a well ventilated area • Keep container tightly closed when not in use • Avoid breathing vapors, spray, or mist • Do not get in eyes, on skin, or on clothing • Wash thoroughly after handling • Do not eat, drink or smoke when using this product • Wear protective gloves, clothing, face and eye protection • Avoid release to the environment (See Safety Data Sheet for complete information)

EMERGENCY & FIRST AID MEASURES:

Get medical attention if exposed and feel unwell, or are concerned. **IF INHALED:** Remove victim to fresh air and keep comfortable for breathing. **IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or physician if feel unwell. **IF ON SKIN (or hair):** If skin irritation occurs: Get medical advice/attention. Wash with

plenty of water. Take off contaminated clothing and wash before reuse. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation occurs: Get medical attention. **IN CASE OF FIRE:** Use water, water fog, dry chemical, CO₂ or alcohol resistant foam to extinguish. (See Safety Data Sheet for complete information)

WARRANTY:

SEK-Surebond warrants its products to substantially conform to its published specifications at the time of purchase. The foregoing is the sole limited warranty applicable to the products. **SEK-SUREBOND HEREBY DISCLAIMS ALL OTHER WARRANTIES OF ANY KIND OR NATURE, WHETHER EXPRESS, IMPLIED, OR STATUTORY, INCLUDING WITHOUT LIMITATION THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ANY OTHER WARRANTY OTHER THAN THE WARRANTY SET FORTH ABOVE.** The user is solely responsible for determining suitability of the products for their particular use. While the actual application of this product is out of the control of SEK-Surebond, it is recommended that the application guidelines be followed completely and accurately. SEK-Surebond's liability for any damage shall not exceed the purchase price of the product used, and it shall have no liability for consequential, incidental or punitive damages.

ASSISTANCE & ADDITIONAL INFORMATION:

For sales, specification assistance, technical questions, detailing, etc., please contact:



3925 Stern Ave.
 St. Charles, IL 60174
 Email: info@sek.us.com
 Fax: 630-762-0607
800-932-3343
 www.sek.us.com

